



by System Sensor

## Model Number Cross-Reference

InnovairFlex™ Model	Description	Sensor	Replaces
<b>D2A</b>	Conventional 2-wire Photoelectric Duct Smoke Detector with Low-flow Tecnology	2151A, Included	DH100LPA
<b>D4120A</b>	Conventional 4-wire Photoelectric Duct Smoke Detector with Low-flow Technology 24VAC/DC, 120VAC	New 2D51A, Included	DH100ACDCLPA, DH100ACDCIA, DH400ACDCA, DH400ACDCIHTA
<b>DNRA</b>	Intelligent Non-relay Photoelectric Duct Smoke Detector with Low-flow Technology	No head included, Intelligent sensor head sold separately	DH200PLA, DH200RPLA
<b>D4SA</b>	Conventional 4-wire Sensor Component Only with Low-flow Technology	New 2D51A, Included	New
<b>D4P120A</b>	Conventional 4-wire Power Component Only	NA	New
<b>DST1</b>	1 ft sampling tube	NA	ST-1
<b>DST1.5</b>	1.5 ft sampling tube	NA	ST-1.5
<b>DST3</b>	3 ft sampling tube	NA	ST-3
<b>DST5</b>	5 ft sampling tube	NA	ST-5
<b>DST10</b>	10 ft sampling tube	NA	ST-10
<b>ETX</b>	1 ft steel exhaust tube	NA	A2440-00